



Eyal Microwave Ltd.

Phone: 972-9-7499100 Fax: 972-9-7493669

Kibbutz Eyal D.N. Hasharon Hatichon 45840 Israel

Web: www.eyal-emi.com Email: emi@eyal-emi.com



SP6T ABS SWITCH

FA-2560-VL

SPECIFICATIONS:

* FREQUENCY RANGE: . . . . .		<b><u>0.1÷2.0</u></b>	GHz
* INSERTION LOSS: . . . . .		<b><u>1.5</u></b>	dB max.
* ISOLATION: . . . . .			
1. RF {in to out}	GHz . . . . .	<b><u>60</u></b>	dB min.
	GHz . . . . .		dB min.
	GHz . . . . .		dB min.
2. RF TO CONTROL . . . . .			dB min.
3. CONTROL TO RF {VIDEO LEAKAGE} : . . . . .			mV p-p max
* VSWR: . . . . .		<b><u>2.0:1</u></b>	max.
TTL CONTROL LOGIC:			
[ X ] INVERTING {0=I.L. 1=ISO.}			
[ ] NON-INVERTING {0=ISO. 1=I.L.}			
NO. OF CONTROL LINES FOR SPDT SWITCH [ ] ONE [ ] TWO			
* SWITCHING SPEED:			
1. Ton - 50% TTL to 90% OF RF VOLTAGE . . . . .		<b><u>35</u></b>	nSec max.
2. Toff - 50% TTL to 10% OF RF VOLTAGE . . . . .		<b><u>35</u></b>	nSec max.
* SWITCHING RATE:			
1. PRF . . . . .		<b><u>4.0</u></b>	MHz max.
2. PULSE WIDTH . . . . .			nSec min.
[ ] HOT SWITCHING [ ] COLD SWITCHING			
* POWER HANDLING:			
1. CW . . . . . at _____ DEG. C . . . . .		<b><u>200</u></b>	mW max.
2. PULSE . . . . . at _____ DEG. C . . . . .			mW max.
PULSE WIDTH . . . . .			mm Sec. min.
DUTY CYCLE . . . . .			%
* HARMONICS: . . . . . at _____ mW POWER INPUT . . . . .			dBc
* POWER SUPPLY:			
	<b><u>160</u></b> mA at	<b><u>+5.0</u></b>	VOLT
	<b><u>100</u></b> mA at	<b><u>-12.0</u></b>	VOLT
* DRIVER: YES			
* TEMPERATURE RANGE:			
STORAGE . . . . .	<b><u>-60</u></b> DEG. C TO	<b><u>+120</u></b>	DEG. C
OPERATING . . . . .	<b><u>-54</u></b> DEG. C TO	<b><u>+85</u></b>	DEG. C

NOTE: