



Eyal Microwave Ltd.

Phone: 972-9-7499100 Fax: 972-9-7493669

Kibbutz Eyal D.N. Hasharon Hatichon 45840 Israel

Web: www.eyal-emi.com Email: emi@eyal-emi.com



WIDEBAND DIGITALLY CONTROLLED ATTENUATOR **MODEL: SA-011-8-0.25**

SPECIFICATIONS

CHARACTERISTIC	
Frequency Range (GHz)	100.0÷1000.0 GHz
Attenuation Range	63.75 dB
Insertion Loss (Max.)	6.0 dB
VSWR (max)	1.8:1
Number of Bits	8
Least Significant Bit (LSB)	0.25 dB
Monotonicity	GUARANTEED
Accuracy of Mean Attenuation	0.5 dB ± 0.125 dB ± 2% 1 to 63.5 dB
Attenuation Flatness	±1.5 dB
Power Handling	20 dBm
Switching Time	500 nSec
Rise and Fall Time	-
Switch Rate	0.5 MHz
Control Logic	“0” = I. Loss “1” = Attn
Control Input	TRUE TTL GATE
Power Supply	+5V = ±2% @ 450 mA
Outline	DC 18
<u>Pin Designations</u>	
E1	0.25 dB
E2	1.5 dB
E3	1.0 dB
E4	2.0 dB
E5	4.0 dB
E6	8.0 dB
E7	16.0 dB
E8	32.0 dB
+V	+5V
G	GROUND